

# DATASHEET

AP-SG408P-2GT-2SF



## 8 Port 10/100/1000 PoE & GE+2SFP Uplink Ports



Model	AP-SG408P-2GE+2SF
Tag Line	8 Ports 10/100/1000 PoE with 2GE+2SFP Uplink Ports
PoE Port:	8 Port 10/100/1000 Base-T PoE
Uplink Port:	2*Gigabit Base-T Port +2*Gigabit Base-X Port
Power Indicator	Light on: Powering Light off: No Power
VLAN Indicator	Green light on: VLAN mode Light off: normal mode
Port 1-10 indicator	Light off: Link is disconnected Red light on: Powering but data disconnected Light flash quickly: Data Transmitting
<b>Standard</b>	
Network Protocol	IEEE802.3i/802.3u/802.3x/802.3af
<b>Performance</b>	
Switching Capacity:	20 Gbps Full duplex
Packet Forwarding Rate:	14.88Mpps/port
Forwarding Mode:	Store-and-forward
MAC Address Table:	2K
VLAN	Support
Watchdog	Support
<b>Power Over Ethernet</b>	
PoE Standard:	IEEE802.3af, IEEE802.3at
PoE Power Supply	1/2(+), 3/6(-)

Model	AP-SG408P-2GE+2SF
Power Over Ethernet	
PoE Standard:	IEEE802.3af, IEEE802.3at
PoE Power Supply	1/2(+), 3/6(-)
Transmission Distance:	0-100m/100Mbps,0-250m/10Mbps after used Extend function
PoE Feature	All ports support MDI/MDIX
General	
Power Source:	Bult-in Power Supply Input: 110-264V AC, 50/60Hz
PoE Power Budget:	96W 52V
Power Consumption:	<5W
ESD	Air discharge: 1.5KV Contact discharge: 1.5KV
Anti-Thunder Level	Air discharge: 1.5KV Contact discharge: 1.5KV
Working Temperature:	-10°C -50°C
Humidity:	10%-95% , non-condensing
Storage Temperature:	-40(-70)
Color	Black
Weight:	0.8kg(not include input cable & packaging)
Dimension(L×W×H):	202*140*45 mm



[www.airpro.in](http://www.airpro.in)