



**GS
1908**

8GE+2SFP Rackmount Switch with 8-Port PoE

- With 8GE+2SFP Ports for High Speed transmit.
- Working with IEEE 802.3af/802.3at compliant PDs.
- Power Supply: 120W.
- Plug and Play.



OVERVIEW

GS1908- 10-Port 10/100/1000Mbps Rackmount Switch with 8-Port PoE provides the seamless network connection. It integrates 8*100/1000Mbps Ethernet capabilities and 2 Gigabit SFP slots for Uplink connection. 8 Auto-Negotiation RJ45 ports of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

KEY FEATURES

- With 8GE+2SFP Ports for High Speed transmit.
- Working with IEEE 802.3af/802.3at compliant PDs.
- Power Supply: 120W.
- Plug and Play.

TECHNICAL SPECIFICATIONS

Hardware	
Data interface	8 10/100/1000Mbps RJ45 Ports 2*10/100/1000Mbps SFP Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) 1000BASE-TX: UTP category 5e,6 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
PoE Ports (RJ45)	Standard: 802.3af/at compliant PoE Ports: Port1- Port8 Power Supply:120W
Background Bandwidth	20Gbps
Power Supply	100-240VAC, 50/60Hz
Dimensions (L x W x H)	285mm*215mm*45mm

Software	
Transfer Method	Store and Forward
MAC Address Table	8K
Advanced Functions	Compatible With IEEE 802.3af/802.3 at Compliant Pds Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode

Others	
Environment	Operating Temperature: 0°C~60°C (32°F~140°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
Package	10-Port 1000Mbps Rackmount Switch with 8-Port PoE Power Adapter User Guide
System Requirements	Microsoft® Windows 8,Windows 7,98SE, NT, 2000, XP, Vista™ , MAC® OS, NetWare®, UNIX® or Linux.



www.airpro.in