

DATASHEET

AP-PA248 PoE Injector



Maximum power for PoE port is 15.4W



TECHNICAL SPECIFICATIONS

Product Model	AP-PA248
Hardware Features	
Standards & Protocols	IEEE802.3af
Interfaces	110/100Mbps RJ45 Port (Data/PoE) 110/100Mbps RJ45 Port (Data)
Input Voltage	AC:100-240V~ 50/60Hz
Output Voltage	DC:48V/0.5A (max)
Power consumption	Power Supply : 15.4W (max)
PoE Supply	PoE Port supports power (maximum power for PoE port is 15.4W)
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F)

Maximum power for PoE port is 30W



TECHNICAL SPECIFICATIONS

Product Model	AP-PA248G
Hardware Features	
Standards & Protocols	IEEE802.3af, IEEE802.3at
Interfaces	110/100/1000Mbps RJ45 Port (Data/PoE) 110/100/1000Mbps RJ45 Port (Data)
Input Voltage	AC:100-240V~ 50/60Hz
Output Voltage	DC:48V/0.8A (max)
Power consumption	Power Supply : 30W (max)
PoE Supply	PoE Port supports standard IEEE802.3at/af power (maximum power for PoE port is 30W)
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F)



www.airpro.in

All specifications in this document are subject to change without notice. AirPro products are sold with a limited warranty described at: www.airpro.in
Copyright 2022-2023, AirPro. All rights reserved.