

L2 Fully Managed PoE Switch

24 x 10/100/1000Base-T PoE + 4 x 100/1000 Base-X (SFP)

QUICK OVERVIEW

AP-SG4500-24GT-P-4SFP is L2 gigabit uplink intelligent switch designed for carrier and MAN networks. It supports comprehensive QoS, enhanced VLAN functions (Dynamic VLAN, Voice VLAN, QinQ, N:1 VLAN Translation etc), Ethernet Ring Protection Protocol (G.8032), classified bandwidth control, intelligent security control, OAM(Operations, Administration and Maintenance), manageability functions and Triple-Play services which fulfill the network requirements demanded by carrier network, MAN access. AP-SG4500-24GT-P-4SFP Series switch offers green features like Fan-less design feature, which can dramatically lower power consumption, achieve green energy and save the cost for the carrier and MAN users.

AP-SG4500-24GT-P-4SFP is equipped with the full GE ports and 4 SFP uplink ports it integrates advanced management and security functions to provide performance and scalability.



FEATURES

- 24x10/100/1000Base-T PoE+4x100/1000Base-X (SFP).
- 1 Console, 1 Reset, 1 USB port.
- PoE+, up to 370w.
- AC power supply.
- Switching capacity: 56Gbps.
- Forwarding rate: 41.7Mbps.

L3 Forwarding

AP-SG4500-24GT-P-4SFP supports L3 forwarding allowing you to segment your network into workgroups and communicate across VLANs without degrading application performance.

VSF (Virtual Switch Framework)

Virtual Switch Framework can virtualize multiple AirPro switches into one logical device, achieving the sharing of information and data tables between different switches. The performance and ports density of the virtualized device is greatly enlarged by times under VSF. VSF also simplifies management work for the network administrator and provides more reliability.

Enhanced Security

IEEE 802.1X port-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using any standard-based RADIUS server.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets and forward by different policies. User-defined ACL provides more flexible access control for users.

AAP-SG4500-24GT-P-4SFP supports DHCP snooping, which prevents DHCP attacks and illegal DHCP SERVER by setting trust ports and untrustports. With DHCP Snooping binding and option82 enabled, it can combine modules like dot1x and ARP, or implement user-access-control independently.

AP-SG4500-24GT-P-4SFP supports abundant L2 security features such as ARP guard, Anti-ARP scanning, and other ARP and MAC Security technology to protect network security and reliability.

High Reliability

AP-SG4500-24GT-P-4SFP supports 4*1G uplink ports, which could be designed to offer redundant uplinks with various ring protection applications, effectively raised the expansibility and performance of the network.

G.8032 provides sub-50ms protection and recovery switching for Ethernet traffic in a carrier ring topology. AP-SG4500-24GT-P-4SFP supports G.8032 v2 and can be deployed in a variety of complex network topologies including single ring, tangent ring, intersecting rings, double rings, and other home networking.

Abundant Multicast Features

AP-SG4500-24GT-P-4SFP also supports MVR (Multicast VLAN Register), selectively allows traffic to cross between different VLANs for bandwidth and security reasons. With the MVR Trunk function, which could associate multicast VLAN to trunk port, AP-SG4500-24GT-P-4SFP combines the VLAN data into the same link, saving lots of resources for users.

AP-SG4500-24GT-P-4SFP could prevent multicast traffic from flooding via IGMP Snooping, while multicast traffic is only forwarded to ports associated with multicast devices.

TECHNICAL SPECIFICATIONS

hardware features		
Items	AP-SG4500-24GT-4SFP	AP-SG4500-24GT-P-4SFP
Ports	24x10/100/1000Base-T +4x100/1000Base-X (SFP) Auto-MIDX 1x Console port 1x USB2.0 interface	24x10/100/1000Base-T PoE +4x100/1000Base-X (SFP) Auto-MIDX 1x Console port 1x USB2.0 interface
Performance		
Switching Capacity	56Gbps	56Gbps
Forwarding Rate	41.7Mbps	
MAC ADDRESS	16K	16K
Jumbo Frame	10K bytes	10K bytes
Packet Buffer	12M Bites	12M Bites
ACL Table	512	512
Queues per port	8	8
VLAN TABLE	4K	4K
Physical		
Dimension (W×H×D)	440mm x 43.6mm x 160mm	440mm x 43.6mm x 260mm
Power Input	100~240VAC, 50~60Hz	100~240VAC, 50~60Hz
Power Consumption	< 20W	< 450W with full PoE output
Cooling	Passive	Active
Temperature	Working 0°C~50°C, Storage -40°C~70°	Working 0°C~50°C, Storage -40°C~70°C
Relative Humidity	5%~95%, non-condensing	5%~95%, non-
condensing		CE, RoHS
EMC Safety	CE, RoHS	
PoE	NA	IEEE 802.3af POE (15.4W) IEEE 802.3at POE+ (30W)

Main Features		
Forwarding		Storage and Forwarding
VLAN		Port-based VLAN, IEEE802.1Q, private VLAN, Protocol VLAN, Voice VLAN, MAC VLAN Normal QinQ, Selective QinQ, Flexible QinQ VLAN Translation, N:1 VLAN Translation
L3 Features		Static Routing, PBR
DHCP		IPv4/IPv6 DHCP Client, IPv4/IPv6 DHCP Relay Option 82, Option 37/38 IPv4/IPv6 DHCP Snooping, IPv4/IPv6 DHCP Server
Reliability	Spanning Tree	802.1D STP, 802.1W RSTP, 802.1S MSTP Root Guard, BPDU Guard, BPDU Forwarding, TCN Filtering
	LACP	64 groups / 8 ports
	L2Ring Protection	Protection ITU-T G.8032 Loopback Detection Fast Link

TECHNICAL SPECIFICATIONS

hardware features		
Multicast		IGMP v1/v2/v3 snooping, IGMP Proxy, IGMP v3 MLD v1/v2 snooping
QoS		8 Queues Per Port Bandwidth Control Flow Redirect Classification based on ACL, VLAN ID, COS, TOS, DSCP, Policing Based on Port and VLAN Single Rate single barrel double color for Policing Remark DSCP, COS/802.1p, Precedence, TOS SP, WRR, SWRR, WDRR for Scheduling

Maintenance and Operation Management	<p>TFTP/FTP</p> <p>CLI, Telnet, Console, Reset</p> <p>Web/SSL (IPv4/IPv6)</p> <p>SSH (IPv4/IPv6)</p> <p>SNMPv1/v2c/v3</p> <p>SNMP Trap</p> <p>Public & Private MIB interface</p> <p>RMON 1,2,3,9</p> <p>Ping, Trace Route</p> <p>Radius Authentication</p> <p>Syslog (IPv4/IPv6)</p> <p>SNTP/NTP (IPv4/IPv6)</p> <p>Dual IMG, Multiple Configuration Files</p> <p>Port Mirror, CPU Mirror, RSPAN</p> <p>sFlow (SG4500-28P/52P)</p> <p>OAM EFM</p> <p>VCT, DDM</p> <p>ULDP(like Cisco UDLD)</p> <p>LLDP/LLDP MED</p>
Green Energy	<p>Fanless</p> <p>Auto-speed Fan</p>



www.airpro.in