



ES-1116

16-PORT FE ETHERNET UNMANAGED SWITCH

- Support 16 10/100BASE-T unmanaged Switch
- External power supply 5V/1A AC adapter
- Complies with IEEE802.3, IEEE802.3u standards.
- Supports MAC address auto-learning and auto-aging.
- LED indicators for monitoring power, link, and activity.



What This Product Does

The Fast Ethernet Switch provides 8 10/100Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. The Switch is Plug-and-Play and each port can be used as general ports or Uplink ports and can be simply plugged into a server, a hub or a switch, using straight cable or crossover cable. Support Loop detection and prevention.

TECHNICAL SPECIFICATIONS

Hardware	
Model No.	ES-1116
Key Components	Realtek RTL8316E
I/O ports	16 x FE Ethernet Ports, RJ45
Standard	IEEE802.3 10BASE-T IEEE802.3u 100BASE-TX Fast Ethernet
SW feature	Support HALF/FULL-Duplex operation IEEE802.3x Flow control Auto negotiation Auto MDI/MDIX Non Blocking
HW Feature	256Kbyte packet buffer 8K MAC address table
LED Define	Power : Green LED - off: power off or fail - on: power on LAN port LED: Green - Off: port disconnected or link fail - Green on: 10/100Mbps connected - Blinking: sending or receiving data
Power Input	5V/1A AC adapter
Dimension	160(W) x 41.5(H) x 107(D) mm
Temperature	Operating: 0 ~ 40°C Storage : -40 ~ 70°C
Humidity	10% ~ 90% RH (non-condensing)



www.airpro.in